

TECHNICAL SPECIFICATIONS FOR THE T SERIES RACKING SYSTEM

STANDARD SIZES

Width (mm)	Fixing Centres (mm)	Depth (mm)	Maximum usable Depth (mm)	Standard Heights	Maximum Loading (kg) approx
600	19" (465)	600	560	12U – 47U	500
600	19" (465)	800	760	12U – 47U	500
600	19" (465)	960	TBC	42U – 47U	500
800	19" (465)	600	560	27U – 47U	500
800	19" (465)	800	760	27U – 47U	500
800	19" (465)	960	TBC	42U – 47U	500

HEIGHT

Internal Height (U)	Internal Height (mm)	External Height With Castors (mm)	External Height Without Castors (mm)
47U	2000.25	2280	2210
42U	1866.90	2055	1985
37U	1644.65	1830	1760
27U	1200.15	1390	1320
18U	800.10	985	915
12U	533.40	720	650

ACCESSORIES AVAILABLE

SHELVES

Shelf Type	Depth (mm)	Load Bearing Capacity (kg)
Standard	350	60
	550	60
	710	60
Sliding Shelf	350	20
	550	20
	710	20
Modem Shelf	1U - 190	30
	2U - 250	30
	2U - 400	30
	4U - 400	30

PLINTH'S

Plinths are available for all cabinets 100mm height, 600mm or 800mm width, 600, 800 or 960mm depth

Cable Management

Cable management rings, used vertically in a cabinet, supplied in a left hand or right hand versions

FAN TRAYS

Roof Fan Trays

2 way or 4 way Roof Tray are available, supplied with 13amp plug and lead.

Front mounting Fan trays

19" Front Mounting fan trays in 2 way or 3 way fans.

CABLE TRAYS

Width	Height
100mm	12U – 47U
150mm	12U – 47U

COLOUR SPECIFICATION

Cabinets available in two Standard colours: (Epoxy powder paint)
Light Grey RAL 7035
Or Black RAL 9004

LEVELLING FEET AND CASTORS

All Cabinets are supplied with med duty castors, which can be changed for Heavy-Duty Castors or Adjustable feet (Packs of 4)