

## Product Datasheet

### MINI DESKTOP UNITS



#### PRODUCT DESCRIPTION

The MINI desktop is designed to be a compact unit, offering mixed choices of individually fused UK power sockets, and a powerful 3.4A USB A+C charger

- Dual A+C US/b charger, with Quick Charge 3.0, and Power Delivery
- Tough extrusion
- 45° angled sockets, can accept large plugs and transformers
- Conforms to BS6396 and BS1363
- Certified to BS5733
- 500mm power lead to male 3-pole connector

#### STANDARD PRODUCTS

Part Code	No. of Power	USB	Dimensions
MINI DESK 2	2 x 5A sockets	N/A	160 x 72 x 78mm
MINI DESK 1U	1 x 5A sockets	Dual 5V 3.4A A+C	160 x 72 x 78mm
MINI DESK U2	3 x 5A sockets	Dual 5V 3.4A A	160 x 72 x 78mm

## INSTALLATION



All desktop units come with 2 methods of attaching to the desktop. Fix to the desk with either a pair of G-Clamps, or using adhesive pads.

The clamps come with an optional rubber guard to protect the desk

## USAGE & MAINTENANCE

Not to be used with products and appliances exceeding 5A

Fuses are 5x20mm and can be user-replaced.

To replace a fuse, disconnect the unit from the mains first.

To clean unit, disconnect from the mains, and wipe with a clean damp cloth

## TECHNICAL SPECIFICATION

In the box	1x Desktop unit; pair of clamps; pair of adhesive pads
Construction	PVC extrusion, PVC sockets and fascias
Max voltage	250V
Fuse rating	3.15A or 5A
Fuse size/type	5x20mm ceramic slow blow
USB	USB output type A and type C, Max 18W USB A: QC3.0, DC 5V3A, 9V2A, 12V1.5A USB C: PD, DC 5V3A, 9V2A, 12V1.5A A+C together: DC5V3.4A
Mains lead length	500mm
Mains lead spec	1.5mm <sup>2</sup> HO5VV-F
Mains connector	20A male 3-pole connector
Conformities	BS 1363; BS 6396:2008; BS 5733; IEC60884-1:2006; UL 94V-0
Switch	Single pole with neon indicator
Compliances	RoHS; WEEE; CE; UKCA