IP1 – OVERALL ENERGY MONITORED POWER DISTRIBUTION UNIT



Designed and manufactured in the UK

Horizontal and Vertical Options

Single / Three Phase Options

Communicate via HTML, HTTPs, SNMP, XML

Multiple Sockets Types Available

Environmental / Security Ports, as Standard

Billing Quality Measurement

Product overview

IPower intelligent PDU,s are designed and manufactured in the UK to provide an easy to use, reliable product set that can be integrated into any market sector.

IPower intelligent PDU,s are constructed to meet clients specific requirements or from our own standard build options for use in new and legacy environments.

Features

- **Overall Energy Measurement**
- Monitor up to 32 PDU's on a single IP Address
- **Fitted and Remote RGB Display Option**
- Free supplied/supported SNMP software
- Phase Balancing information

- Constructed using any socket type
- **T** Receive email Alerts
- Easily configured and setup in minutes
- Simple migration to full DCiM
- Alerts on all set parameters



Energy Metrics

iPower IP1 overall monitored PDU's measure and allow min/max level thresholds to be set for:

- **RMS Volts**
- **RMS Amps**
- **Kilowatts**
- Internal Temperature
 - Frequency Power Factor

Additional measurements include:-

- Peak Volts
- Peak Current
- kVA

Cumulative values include:-

- kWh • kJ/H
- BTU/h kg/CO2
- Consumption cost

iPower covers the requirements for cabinet

Environmental

iPower comes with comprehensive environmental monitoring including ports for:-

- 8 x Temperature sensors. 1 x Humidity/Temp sensor

Communication

 Communicates over SNMPHTTP, HTML and XML via inbuilt WEB Browser

• Supplied MIB for integration into 3rd party DCiM • Full DCiM solution available



security with ports for:-

Security

Build Standard

- Full CE/WEEE/RoSH compliant
- Manufactured to BS EN 60950-1