

ICON LINK Under-Desk

Modular UK power with resettable thermal fuses



KEY FEATURES

- 3.15A resettable thermal fuses
- 2, 3, 4 and 6-way versions
- 3-pole input / output
- 150mm earth lead to ring terminal
- End mounting brackets
- Daisy-chain using INTER leads

Under-desk UK power modules with individually protected outlets. The mounting brackets support direct fixing beneath a desk or cable tying into a wire basket.

Standard models

Part number	Description	Dimensions
ICON LINK 2	2 UK sockets; 3.15A resettable thermal fuses	197 x 43 x 62mm
ICON LINK 3	3 UK sockets; 3.15A resettable thermal fuses	264 x 43 x 62mm
ICON LINK 4	4 UK sockets; 3.15A resettable thermal fuses	316 x 43 x 62mm
ICON LINK 6	6 UK sockets; 3.15A resettable thermal fuses	435 x 43 x 62mm

ICON LINK Under-Desk

Technical specification

Specification	Details
Construction	PVC extrusion, PVC sockets and fascias
Maximum voltage	250V
Fuse	3.15A resettable thermal
Mains connector	20A male 3-pole connector
Source conformity references	BS 1363; BS 6396:2008; BS 5733; IEC 60884-1:2006; UL 94V-0
Source compliance marks	RoHS; WEEE; CE; UKCA

Use and maintenance

Do not connect an appliance exceeding 3.15A. A red fuse indicator shows that the thermal fuse needs resetting. Disconnect the unit from the mains, then use a tool to depress the red indicator until it clicks. Reconnect after resetting. Disconnect before cleaning and wipe with a clean damp cloth.