

IEC C19 PDUs

Rack power distribution units



KEY FEATURES

- IEC 320 C19 sockets
- Horizontal and vertical models
- 1.5U aluminium extrusion
- Shrouded switch and cover
- 3m lead on standard models
- Alternative input plugs available

IEC C19 distribution for compatible equipment in network and server cabinets. Select a horizontal or vertical unit to suit the installation.

Standard models

Part number	Description
HC19/6	Horizontal; 6 IEC C19 sockets; 3m lead to IEC C20 plug
HC19/8	Horizontal; 8 IEC C19 sockets; 3m lead to IEC C20 plug
VC19/10	Vertical; 10 IEC C19 sockets; 3m lead to IEC C20 plug

Input plug options

IEC C20, 16A Commando, Schuko/French CEE 7/7, or 32A Commando. The source states that internal wiring is upgraded for the 32A option.

IEC C19 PDUs

Technical specification

Specification	Details
Net weight	1.35-1.65kg
Net dimensions (L x W x D)	486-658 x 66 x 44mm
Shipping dimensions (L x W x D)	540-750 x 122-142 x 60-68mm
Shipping weight	1.5-1.9kg
Source maximum power	3250W
Socket output rating	16A
Overall rating stated	16A
Input frequency	50/60Hz
Acceptable input voltage	250VAC

Rating information

Ratings and dimensions below are reproduced from the source range sheet. The fitted input connector and lead determine the permitted supply rating.