

MINI Desktop Units

Compact desktop power and USB charging



KEY FEATURES

- Individually fused UK sockets
- 45° angled socket faces
- 500mm lead to 3-pole connector
- Desk clamp or adhesive-pad fixing
- 160 x 72 x 78mm body
- USB-equipped options

A compact desktop module offering UK power and USB charging options. This redesigned sheet retains the model information from the named source version.

Standard models

Part number	Power sockets	USB
MINI DESK 2	2 x 5A sockets	None
MINI DESK 1U	1 x 5A socket	Dual 5V/3.4A A+C
MINI DESK U2	None - USB only	Dual 5V/3.4A A

Dimensions

All listed models: 160 x 72 x 78mm.

MINI Desktop Units

Technical specification

Specification	Details
In the box	Desktop unit, pair of clamps and pair of adhesive pads
Construction	PVC extrusion, PVC sockets and fascias
Maximum voltage	250V
Fuse rating	3.15A or 5A, according to model
Fuse type	5 x 20mm ceramic slow-blow
USB charging	USB-A QC 3.0: 5V/3A, 9V/2A, 12V/1.5A. USB-C PD: 5V/3A, 9V/2A, 12V/1.5A. Maximum 18W; A+C together: 5V/3.4A.
Mains lead	500mm; 1.5mm ² H05VV-F
Mains connector	20A male 3-pole connector
Switch	Single pole with neon indicator
Source conformity references	BS 1363; BS 6396:2008; BS 5733; IEC 60884-1:2006; UL 94V-0
Source compliance marks	RoHS; WEEE; CE; UKCA

Installation

Fix to the desktop using the supplied pair of G-clamps or adhesive pads. Optional rubber guards protect the desk at the clamps.

Use and maintenance

Observe the individual socket fuse rating: do not connect an appliance exceeding that rating. Disconnect from the mains before replacing a fuse or cleaning. Use the specified 5 x 20mm replacement fuse. Wipe with a clean damp cloth.