

P-Pack Desktop Power, Data & USB

Desktop UK power with USB-A and USB-C charging



KEY FEATURES

- Individually fused UK sockets
- 45° angled socket faces
- 500mm lead to 3-pole connector
- Desk clamp or adhesive-pad fixing
- USB-A QC 3.0 and USB-C PD
- Black/grey and white options

An angled desktop power module with individually fused UK outlets and dual USB charging. Cat 6 couplers provide direct data connections.

Standard models

Part number	Sockets / data	Colour	Dimensions
P-Pack Desk 2/2SU	2 x 5A sockets; 2 Cat 6	Black/grey	326 x 72 x 78mm
P-Pack Desk 2/2WU	2 x 5A sockets; 2 Cat 6	White	326 x 72 x 78mm
P-Pack Desk 3/2SU	3 x 5A sockets; 2 Cat 6	Black/grey	409 x 72 x 78mm
P-Pack Desk 3/2WU	3 x 5A sockets; 2 Cat 6	White	409 x 72 x 78mm
P-Pack Desk 4/2SU	4 x 5A sockets; 2 Cat 6	Black/grey	458 x 72 x 78mm
P-Pack Desk 4/2WU	4 x 5A sockets; 2 Cat 6	White	458 x 72 x 78mm
P-Pack Desk 4/4SU	4 x 5A sockets; 4 Cat 6	Black/grey	518 x 72 x 78mm
P-Pack Desk 4/4WU	4 x 5A sockets; 4 Cat 6	White	518 x 72 x 78mm

USB fitted to all listed models

Dual USB-A + USB-C charger. Combined output: 5V/3.4A; maximum single-port output: 18W.

P-Pack Desktop Power, Data & USB

Technical specification

Specification	Details
In the box	Desktop unit, pair of clamps and pair of adhesive pads
Construction	PVC extrusion, PVC sockets and fascias
Maximum voltage	250V
Fuse rating	3.15A or 5A, according to model
Fuse type	5 x 20mm ceramic slow-blow
USB charging	USB-A QC 3.0: 5V/3A, 9V/2A, 12V/1.5A. USB-C PD: 5V/3A, 9V/2A, 12V/1.5A. Maximum 18W; A+C together: 5V/3.4A.
Mains lead	500mm; 1.5mm ² H05VV-F
Mains connector	20A male 3-pole connector
Switch	Single pole with neon indicator
Source conformity references	BS 1363; BS 6396:2008; BS 5733; IEC 60884-1:2006; UL 94V-0
Source compliance marks	RoHS; WEEE; CE; UKCA

Installation

Fix to the desktop using the supplied pair of G-clamps or adhesive pads. Optional rubber guards protect the desk at the clamps.

Use and maintenance

Observe the individual socket fuse rating: do not connect an appliance exceeding that rating. Disconnect from the mains before replacing a fuse or cleaning. Use the specified 5 x 20mm replacement fuse. Wipe with a clean damp cloth.