

P-Pack Power & Cat 6

Under-desk modules with optional USB charging



KEY FEATURES

- Individually fused UK sockets
- Two Cat 6 socket-to-socket links
- 3-pole power input
- 2, 4 or 6 UK sockets
- Optional USB-A + USB-C charging
- 18W maximum combined USB output

Internal Cat 6 input/output assemblies simplify installation. Power is supplied through a 3-pole connector using a START mains lead. USB-equipped versions add smart USB-A and USB-C charging.

Standard models

Part number	Description
P-Pack 2/2DC	2 UK sockets, individually 5A fused; 2 Cat 6 assemblies
P-Pack 4/2DC	4 UK sockets, individually 5A fused; 2 Cat 6 assemblies
P-Pack 6/2DC	6 UK sockets, individually 3.15A fused; 2 Cat 6 assemblies
P-Pack 2/2DCU	2 UK sockets, individually 5A fused; 2 Cat 6 assemblies; dual USB A+C
P-Pack 4/2DCU	4 UK sockets, individually 5A fused; 2 Cat 6 assemblies; dual USB A+C
P-Pack 6/2DCU	6 UK sockets, individually 3.15A fused; 2 Cat 6 assemblies; dual USB A+C

Technical specification

Specification	Details
USB functions	USB-A / USB-C QC 3.0; USB-C PD; 18W maximum total A+C output
Source protocol references	BC1.2; PD2.0; QC3.0; Apple protocols
Source standard references	BS 6396:2022; BS 5733 approval