

PD Surface

Recessed desk power with USB and data options



KEY FEATURES

- Individually fused UK sockets
- Dual 2.1A USB charging
- GST18 input and output
- 6C data / multimedia options
- Socket orientation choices
- Fits desktops 25-90mm thick

PD Surface fits into the desktop to provide power and data at the point of use. GST18 input and output allow compatible units to be linked. Optional 6C positions accept data or multimedia modules.

Standard models

Part number	Description
PD Surface 2U	2 individually fused UK sockets; dual USB
PD Surface 2/46CU	2 individually fused UK sockets; 4 x 6C; dual USB
PD Surface 4U	4 individually fused UK sockets; dual USB
PD Surface 4/2U	4 UK sockets oriented N/S/N/S; 2 dual USB chargers
PD Surface 4/46CU	4 individually fused UK sockets; 4 x 6C; dual USB
PD Surface 6/2U	6 UK sockets oriented N/S/N/S/N/S; 2 dual USB chargers

PD Surface

Multimedia options

Part number	Description
6C/B	Black 6C blank
6C/C6	Black Cat 6 fascia and coupler
6C/6C	Black Cat 6 IDC data module
6C/C63	3m Cat 6 assembly with black 6C fascia
6C/C65	5m Cat 6 assembly with black 6C fascia
6C/V	300mm VGA launch lead
6C/U	300mm USB launch lead
6C/H	300mm HDMI launch lead
6C/3.5	300mm 3.5mm jack launch lead

Installation

Under-desk ratchet system fits desktops from 25mm to 90mm thick. Socket orientation options suit meeting and boardroom arrangements.

Source standard reference

Individually fused to BS 6396:2008, as stated in the source sheet.