

Vertical UK PDUs

UK socket cabinet power distribution



KEY FEATURES

- Right-angled, left-hand UK sockets
- Aluminium extrusion
- Shrouded switch and cover
- External earthing point
- 3m 1.5mm² lead options
- 20mm gland-entry versions

A vertical UK socket PDU for mounting at the rear of a cabinet without occupying rack units. Gland-entry versions provide a connecting block for a separately specified feed.

Standard models

Part number	Description
V13A/4	4 UK 13A sockets; switch; 3m lead to UK 13A plug
V13A/4/20	4 UK 13A sockets; 20mm gland hole with internal connecting block
V13A/5	5 UK 13A sockets; switch; 3m lead to UK 13A plug
V13A/5/20	5 UK 13A sockets; 20mm gland hole with internal connecting block
V13A/6	6 UK 13A sockets; switch; 3m lead to UK 13A plug
V13A/6/20	6 UK 13A sockets; 20mm gland hole with internal connecting block

Alternative input plugs

IEC C14 / C20 (IEC 60320) or 16A Commando (IEC 60309).

Vertical UK PDUs

Technical specification

Specification	Details
Net weight	0.95kg
Net dimensions (L x W x D)	490 x 60 x 45mm
Shipping dimensions (L x W x D)	515 x 150 x 70mm
Shipping weight	1.1kg
Source maximum power	3250W
Socket output rating	13A
Overall rating stated	16A
Input frequency	50/60Hz
Acceptable input voltage	250VAC

Rating information

Ratings and dimensions below are reproduced from the source range sheet. The fitted input connector and lead determine the permitted supply rating.