

Vertical UK PDU

Picture shows V13A/4

- Vertical UK BS1363 right-angled, left hand sockets
- Tough aluminium extrusion
- Shrouded switch and switch cover
- 3m 1.5mm cable, C14, C20, or 16A commando plug
- 20mm gland hole with 3-way connecting block option
- External earthing point

Vertical UK PDUs are widely used to accommodate cabinets where a higher number of UK sockets are needed, but rack space is also at a premium. Being mounted at the back of the cabinet means that the PDU maintains a '0U' profile, allowing the rest of the cabinet to be populated with critical hardware. Likewise, the no cable, 20mm version allows the specifier to deliver power to the desk from a tap off lead or whatever.


Standard products

Order Code

Product Description

V13A/4	4-way UK 13A sockets with switch to 3-metre lead to 13A plug
V13A/4/20	4-way UK 13A sockets. 20mm gland hole with choc block inside
V13A/5	5-way UK 13A sockets with switch to 3-metre lead to 13A plug
V13A/5/20	5-way UK 13A sockets. 20mm gland hole with choc block inside
V13A/6	6-way UK 13A sockets with switch to 3-metre lead to 13A plug
V13A/6/20	6-way UK 13A sockets. 20mm gland hole with choc block inside


PDU options



IEC C14 plug
IEC 60320(320)



16A commando plug
IEC 60309(309)



IEC C20 plug
IEC 60320(320)



PDU technical data

Weight of PDU	0.95kg
Net length of PDU	490mm
Net width of PDU	60mm
Net depth of PDU	45mm
Shipping length of PDU	515mm
Shipping Width of PDU	150mm
Shipping Depth of PDU	70mm
Shipping Weight of PDU	1.1kg
PDU max power	3250W
Output rating	13A
Overall rating	16A
Input Frequency	50/60Hz
Acceptable Input Voltage	250VAC