

32A UK PDUs

Rack power distribution units



KEY FEATURES

- Horizontal and vertical formats
- 1.5U aluminium extrusion
- Neon power indicator
- 3m 4mm² supply lead
- 2.5mm² internal ring wiring
- 32A Commando input

Source image: V13A/12/32A

UK socket power distribution for data centres and comms rooms using a 32A supply. Upgraded external cable and internal ring wiring support the higher input rating.

Standard models

Part number	Description
H13A/6/32A	Horizontal 6-way UK PDU
V13A/8/32A	Vertical 8-way UK PDU
V13A/10/32A	Vertical 10-way UK PDU
V13A/12/32A	Vertical 12-way UK PDU
V13A/16/32A	Vertical 16-way UK PDU
V13A/20/32A	Vertical 20-way UK PDU

Supply lead

All listed models: 3m 4mm² lead terminated with a 32A Commando plug.

32A UK PDUs

Technical specification

Specification	Details
Net weight	1.7-2.65kg
Net dimensions (L x W x D)	486-1330 x 65 x 45mm
Shipping dimensions (L x W x D)	540-1385 x 142-155 x 65-75mm
Shipping weight	1.85-3.2kg
Source maximum power	8000W
Socket output rating	13A
Overall rating stated	32A
Input frequency	50/60Hz
Acceptable input voltage	250VAC

Rating information

Ratings and dimensions below are reproduced from the source range sheet. The fitted input connector and lead determine the permitted supply rating.