Horizontal UK PDUs

Rack power distribution units



KEY FEATURES

- UK BS 1363 Type G outlets
- 1.5U aluminium extrusion
- Shrouded switch and cover
- Rear cable exit
- 3m 1.5mm² lead
- Alternative input plugs available

Horizontal UK BS 1363 Type G power distribution from one accessible point in the rack. A rear cable exit simplifies mounting while the body occupies 1.5U.

Standard models

Part number	Description
H13A/4	4-way UK BS 1363 Type G PDU; switch; 3m lead to UK 13A plug
H13A/5	5-way UK BS 1363 Type G PDU; switch; 3m lead to UK 13A plug
H13A/6	6-way UK BS 1363 Type G PDU; switch; 3m lead to UK 13A plug

Input plug options

IEC C14 (IEC 320), IEC C20 (IEC 320), 16A Commando (IEC 309), or Schuko/French CEE 7/7.

Horizontal UK PDUs

Technical specification

Specification	Details
Net weight	1.1-1.15kg
Net dimensions (L x W x D)	490 x 60 x 45mm
Shipping dimensions (L x W x D)	520 x 132 x 75mm
Shipping weight	1.3-1.35kg
Source maximum power	3250W
Socket output rating	13A
Overall rating stated	16A
Input frequency	50/60Hz
Acceptable input voltage	250VAC

Rating information

Ratings and dimensions below are reproduced from the source range sheet. The fitted input connector and lead determine the permitted supply rating.